

Hydrostatic pressure transmitter FRIPRO P21

Made in Germany!



Output signal

- 1 0...10 V 3-wire
- 4 4...20 mA 2-wire (signal range 3.7...20.5 mA)
- 8 0...5 V 3-wire
- A 0.5...4.5 V 3-wire, ratiometric

Range

- Measurement range see table
- 99 non-standard range

Process connection and material

- 1 G 1/2 A DIN 3852 1.4404 (316L)
- 2 1/2-14 NPT 1.4404 (316L) (on request)
- F G 1 A DIN 3852 1.4404 (316L) (on request)
- Q G 3/4" DIN 3852 1.4404 (316L) (on request)
- X Clamp DIN DN 10...20, 1.4404 (316L)
- 9 others (on request)

Sensor seal

- 1 FPM (Viton) standard
- 2 NBR (Nitril)
- 3 EPDM (Kautschuk)
- 9 others (on request)

Electrical connection

- 0 5m cable, IP 67
- 1 Connector EN 175301-803A IP 67
- 6 2m cable IP 67
- A Connector M12x1, IP 67
- F Quickon-Connector IP 67
- H 10m Cable, IP 67
- 9 others (on request)

Pottet electronic

- 0 without pottet electronic
- 1 pottet electronic

