

Digital-contact manometer FRIPRO PM82

Made in Germany!



Ordering Required Fields:

Analog output signal

- 0 without
- 1 0...10V 3-wire
- 2 0...20 mA 3-wire
- 3 4...20 mA 3-wire (signal range 3.8...20.5 mA)

Contact output

- 1 single
- 2 double

Ranges

- see table
- 99 non standard range (on request)

Process connection and material

- 3 G 1/2 B DIN 16288 1.4404
- M Dairy thread ND 25 DIN 11851 1.4404
- 6 Dairy thread ND 32 DIN 11851 1.4404
- 7 Dairy thread ND 40 DIN 11851 1.4404
- K Dairy thread ND 40 aseptisch 1.4404
- N DRD flange ND 65 1.4404
- J Varivent DN 68 1.4404
- L Clamp 1", ND 25...40, 1.4404
- W Clamp 2", ND 50, 1.4404
- 9 others on request

Sensor seal

- 1 FPM (Viton) standard
- 2 NBR (Nitril)
- 3 EPDM-Kautschuk
- 4 Fluor-Silikon-Rubber
- 5 Chemraz 505
- 9 others on request

Options

- 0 Display 3 digits
- 1 Display reduced to 2 digits

PM82 - -

www.fripro.eu